EXHIBIT 3

US009344206B2

(12) **United States Patent**
Lambourne

(10) **Patent No.: US 9,344,206 B2**
(45) **Date of Patent: May 17, 2016**

(54) **METHOD AND APPARATUS FOR UPDATING ZONE CONFIGURATIONS IN A MULTI-ZONE SYSTEM**

(71) Applicant: **Sonos, Inc**, Santa Barbara, CA (US)

(72) Inventor: **Robert A. Lambourne**, Santa Barbara, CA (US)

(73) Assignee: **Sonos, Inc.**, Santa Barbara, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/465,457**

(22) Filed: **Aug. 21, 2014**

(65) **Prior Publication Data**

US 2014/0361867 A1 Dec. 11, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/896,829, filed on May 17, 2013, which is a continuation of application No. 11/853,790, filed on Sep. 11, 2007, now Pat. No. 8,483,853.

(60) Provisional application No. 60/825,407, filed on Sep. 12, 2006.

(51) **Int. Cl.**
G06F 17/00 (2006.01)
H04H 60/80 (2008.01)
(Continued)

(52) **U.S. Cl.**
CPC ***H04H 60/80*** (2013.01); ***G05B 15/02*** (2013.01); ***G06F 3/0482*** (2013.01); ***G06F 3/04842*** (2013.01); ***G06F 3/16*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04H 60/80; H05B 15/02; H04R 3/12; H04R 27/00; H04R 2227/005; H04R 2430/01; H03G 7/00; H03G 1/02; G06F 3/16; G06F 3/165; G06F 3/0482; G06F 3/04842; H04N 21/43615
USPC 700/94; 381/120, 80; 715/716, 727
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,182,552 A 1/1993 Paynting
5,406,634 A 4/1995 Anderson et al.
(Continued)

FOREIGN PATENT DOCUMENTS

JP 2009218888 9/2009
JP 2011176581 9/2011
(Continued)

OTHER PUBLICATIONS

Dynaudio Air series speakers; copyright and available for sale at least 2002.*
(Continued)

Primary Examiner — Paul McCord
(74) *Attorney, Agent, or Firm* — McDonnell, Boehnen, Hulbert & Berghoff LLP

(57) **ABSTRACT**

In general, techniques of controlling a plurality of multimedia players in groups are disclosed. According to one aspect of the present invention, a mechanism is provided to allow a user to group some of the players according to a theme or scene, where each of the players is located in a zone. When the scene is activated, the players in the scene react in a synchronized manner. For example, the players in the scene are all caused to play a multimedia source or music in a playlist, wherein the multimedia source may be located anywhere on a network.

20 Claims, 11 Drawing Sheets



(51) **Int. Cl.**

G05B 15/02	(2006.01)
H04R 3/12	(2006.01)
G06F 3/16	(2006.01)
H03G 7/00	(2006.01)
H04N 21/436	(2011.01)
G06F 3/0482	(2013.01)
G06F 3/0484	(2013.01)
H03G 1/02	(2006.01)
H04R 27/00	(2006.01)

(52) **U.S. Cl.**

CPC ***G06F 3/165*** (2013.01); ***H03G 1/02*** (2013.01); ***H03G 7/00*** (2013.01); ***H04N 21/43615*** (2013.01); ***H04R 3/12*** (2013.01); ***H04R 27/00*** (2013.01); *H04R 2227/005* (2013.01); *H04R 2430/01* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,519,641	A	5/1996	Beers et al.	
5,923,902	A	7/1999	Inagaki	
5,946,343	A	8/1999	Schotz et al.	
6,256,554	B1	7/2001	DiLorenzo	
6,404,811	B1	6/2002	Cvetko et al.	
6,487,296	B1	11/2002	Allen et al.	
6,522,886	B1	2/2003	Youngs et al.	
6,587,127	B1	7/2003	Leeke et al.	
6,604,023	B1	8/2003	Brown et al.	
6,611,537	B1	8/2003	Edens et al.	
6,631,410	B1	10/2003	Kowalski et al.	
6,757,517	B2	6/2004	Chang	
6,778,869	B2	8/2004	Champion	
6,889,207	B2	5/2005	Slemmer et al.	
7,130,608	B2	10/2006	Hollstrom et al.	
7,130,616	B2	10/2006	Janik	
7,143,939	B2	12/2006	Henzerling	
7,187,947	B1	3/2007	White et al.	
7,218,708	B2	5/2007	Berezowski et al.	
7,236,773	B2	6/2007	Thomas	
7,302,468	B2	11/2007	Wijeratne	
7,346,332	B2 *	3/2008	McCarty et al.	455/402
7,483,538	B2	1/2009	McCarty et al.	
7,539,551	B2	5/2009	Komura et al.	
7,558,224	B1	7/2009	Surazski et al.	
7,561,932	B1 *	7/2009	Holmes et al.	700/94
7,571,014	B1	8/2009	Lambourne et al.	
7,626,952	B2	12/2009	Slemmer et al.	
7,643,894	B2	1/2010	Braithwaite et al.	
7,657,910	B1	2/2010	McAulay et al.	
7,668,990	B2	2/2010	Krizyzanowski et al.	
7,689,305	B2	3/2010	Kreifeldt et al.	
7,742,832	B1	6/2010	Feldman et al.	
7,761,176	B2	7/2010	Ben-Yaacov et al.	
7,804,972	B2	9/2010	Melanson	
7,805,210	B2	9/2010	Cucos et al.	
7,817,960	B2	10/2010	Tan et al.	
7,849,181	B2	12/2010	Slemmer et al.	
7,853,341	B2	12/2010	McCarty et al.	
7,962,482	B2	6/2011	Handman et al.	
8,014,423	B2	9/2011	Thaler et al.	
8,045,952	B2	10/2011	Qureshey et al.	
8,054,987	B2	11/2011	Seydoux	
8,086,287	B2	12/2011	Mooney et al.	
8,103,009	B2	1/2012	McCarty et al.	
8,135,141	B2	3/2012	Shiba	
8,189,824	B2	5/2012	Strauss et al.	
8,233,635	B2	7/2012	Shiba	
8,234,395	B2	7/2012	Millington	
8,239,559	B2	8/2012	Rajapakse	
8,290,603	B1	10/2012	Lambourne	
8,423,893	B2	4/2013	Ramsay et al.	
8,483,853	B1	7/2013	Lambourne	
8,498,726	B2	7/2013	Kim et al.	
8,588,432	B1	11/2013	Simon	
8,700,730	B2	4/2014	Rowe	
8,762,565	B2	6/2014	Togashi et al.	
8,788,080	B1	7/2014	Kallai et al.	
8,965,544	B2	2/2015	Ramsay	
2001/0042107	A1	11/2001	Palm	
2002/0002039	A1	1/2002	Qureshey et al.	
2002/0003548	A1	1/2002	Krusche et al.	
2002/0022453	A1	2/2002	Balog	
2002/0026442	A1	2/2002	Lipscomb	
2002/0072816	A1	6/2002	Shdema et al.	
2002/0098878	A1	7/2002	Mooney et al.	
2002/0124097	A1	9/2002	Isely et al.	
2002/0143547	A1 *	10/2002	Fay et al.	704/270
2003/0020763	A1	1/2003	Mayer et al.	
2003/0157951	A1	8/2003	Hasty, Jr.	
2003/0167335	A1	9/2003	Alexander	
2003/0177889	A1	9/2003	Koseki et al.	
2003/0198257	A1	10/2003	Sullivan et al.	
2004/0010727	A1	1/2004	Fujinami	
2004/0015252	A1	1/2004	Aiso et al.	
2004/0024478	A1	2/2004	Hans	
2004/0117044	A1	6/2004	Konetski	
2004/0131192	A1	7/2004	Metcalf	
2004/0147224	A1 *	7/2004	Lee	455/41.3
2004/0220687	A1 *	11/2004	Klotz et al.	700/94
2004/0223622	A1	11/2004	Lindemann et al.	
2004/0225389	A1	11/2004	Ledoux et al.	
2005/0002535	A1	1/2005	Liu et al.	
2005/0021470	A1	1/2005	Martin et al.	
2005/0100174	A1	5/2005	Howard et al.	
2005/0131558	A1	6/2005	Braithwaite et al.	
2005/0144284	A1	6/2005	Ludwig et al.	
2005/0177256	A1	8/2005	Shintani et al.	
2005/0254505	A1	11/2005	Chang et al.	
2005/0289244	A1	12/2005	Sahu et al.	
2006/0041616	A1	2/2006	Ludwig et al.	
2006/0149402	A1	7/2006	Chung	
2006/0179160	A1	8/2006	Uehara et al.	
2006/0205349	A1	9/2006	Passier et al.	
2006/0229752	A1	10/2006	Chung	
2007/0142022	A1	6/2007	Madonna et al.	
2007/0142944	A1	6/2007	Goldberg et al.	
2007/0189544	A1	8/2007	Rosenberg	
2007/0223725	A1	9/2007	Neumann et al.	
2007/0288610	A1	12/2007	Saint Clair et al.	
2008/0025535	A1	1/2008	Rajapakse	
2008/0045140	A1	2/2008	Korhonen	
2008/0066094	A1	3/2008	Igoe	
2008/0066120	A1	3/2008	Igoe	
2008/0077261	A1	3/2008	Baudino et al.	
2008/0092204	A1 *	4/2008	Bryce et al.	725/143
2008/0144861	A1	6/2008	Melanson et al.	
2008/0152165	A1	6/2008	Zacchi	
2008/0159545	A1	7/2008	Takumai et al.	
2008/0162668	A1	7/2008	Miller	
2009/0097672	A1	4/2009	Buil et al.	
2009/0228919	A1	9/2009	Zott et al.	
2009/0232326	A1	9/2009	Gordon et al.	
2010/0010651	A1	1/2010	Kirkeby et al.	
2010/0052843	A1	3/2010	Cannistraro	
2010/0153097	A1	6/2010	Hotho et al.	
2010/0284389	A1	11/2010	Ramsay et al.	
2010/0299639	A1	11/2010	Ramsay et al.	
2012/0047435	A1	2/2012	Holladay et al.	
2013/0253679	A1	9/2013	Lambourne	
2013/0293345	A1	11/2013	Lambourne	

FOREIGN PATENT DOCUMENTS

WO	0153994	7/2001
WO	2005013047	2/2005
WO	2012137190	10/2012

OTHER PUBLICATIONS

Bluetooth, "Specification of the Bluetooth System: The ad hoc SCATTERNET for affordable and highly functional wireless connectivity" Core, Version 1.0 A, Jul. 26, 1999, 1068 pages.(Document

(56) **References Cited**

OTHER PUBLICATIONS

uploaded in 7 different files: NPL1_part1 pp. 1 to 150, NPL1_part2 pp. 151 to 300, NPL1_part3 pp. 301 to 450, NPL1_part4 pp. 451 to 600,NPL1_part5 pp. 601 to 750, NPL1_part6 pp. 751 to 900 and NPL1_part7 pp. 901 to 1068).

Bluetooth. "Specification of the Bluetooth System: Wireless connections made easy" Core, Version 1.0 B, Dec. 1, 1999, 1081 pages. (Document uploaded in 8 different files: NPL2_part1 pp. 1 to 150, NPL2_part2 pp. 151 to 303, NPL2_part3 pp. 304 to 453, NPL2_part4 pp. 454 to 603,NPL2_part5 pp. 604 to 703, NPL2_part6 pp. 704 to 854 and NPL2_part7 pp. 855 to 1005, NPL2_part8 pp. 1006 to 1081).

Dell, Inc., "Dell Digital Audio Receiver: Reference Guide", Jun. 2000, 70 pages.

Dell, Inc., "Start Here", Jun. 2000, 2 pages.

Jones, Stephen, "Dell Digital Audio Receiver: Digital upgrade for your analog stereo" Analog Stereo, Jun. 24, 2000 < http://www.reviewsonline.com/articles/961906864.htm> retrieved Jun. 18, 2014, 2 pages.

Louderback, Jim, "Affordable Audio Receiver Furnishes Homes With MP3",TechTV Vault, Jun. 28, 2000 <http://www.g4tv.com/articles/17923/affordable-audio-receiver-furnishes-homes-with-mp3/> retrieved Jul. 10, 2014, 2 pages.

United States Patent and Trademark Office, "Non-Final Office Action", issued in connection with U.S. Appl. No. 13/896,037, mailed on Feb. 13, 2014, 10 pages.

United States Patent and Trademark Office, "Non-Final Office Action", issued in connection with U.S. Appl. No. 13/892,230, mailed on May 9, 2014, 10 pages.

United States Patent and Trademark Office, "Notice of Allowance", issued in connection with U.S. Appl. No. 13/896,037, mailed on Oct. 28, 2014, 7 pages.

Palm, Inc., "Handbook for the Palm VII Handheld", May 2000, 311 pages.

Higgins et al., "Presentations at WinHEC 2000" May 2000, 138 pages.

The United States Patent and Trademark Office, "Non-Final Office Action", issued in connection with U.S. Appl. No. 13/013,740, mailed on Feb. 10, 2014, 13 pages.

Rane: DragNet software; available for sale at least 2006, 8 pages.

Yamaha DME Designer software manual: Copyright 2004, 482 pages.

Co-pending U.S. Appl. No. 13/083,499, filed Apr. 8, 2011, 69 pages.

The United States Patent and Trademark Office, "Final Office Action", issued in connection with U.S. Appl. No. 13/013,740, mailed on Feb. 10, 2014, 13 pages.

International Bureau, "International preliminary report on patentability," issued in connection with International Patent Application No. PCT/182012/052071, mailed Oct. 17, 2013, 7 pages.

The United States Patent and Trademark Office, "Non-Final Office Action", issued in connection with U.S. Appl. No. 13/013,740, mailed on Sep. 27, 2013, 12 pages.

International Bureau, "Search Report", issued in connection with PCT Application No. PCT/IB2012/052071, mailed on Aug. 23, 2012, 3 pages.

Jo J., et al., "Synchronized One-to-many Media Streaming with Adaptive Playout Control," Proceedings of SPIE, 2002, vol. 4861, pp. 71-82.

Mills D.L., "Network Time Protocol (Version 3) Specification, Implementation and Analysis," Network Working Group, Mar. 1992, <http://www.ietf.org/rfc/rfc1305.txt>, 7 pages.

"Polycom Conference Composer manual: copyright 2001", 29 pages.

International Bureau, "Written Opinion", issued in connection with PCT Application No. PCT/IB2012/052071, mailed on Aug. 23, 2012, 6 pages.

The United States Patent and Trademark Office, "Advisory Action", issued in connection with U.S. Appl. No. 11/853,790, mailed Dec. 22, 2011, 3 pages.

The United States Patent and Trademark Office, "Final Office Action", issued in connection with U.S. Appl. No. 11/853,790, mailed Oct. 13, 2011, 9 pages.

The United States Patent and Trademark Office, "Notice of Allowance", issued in connection with U.S. Appl. No. 11/853,790, mailed Apr. 18, 2013, 8 pages.

The United States Patent and Trademark Office, "Non-Final Office Action", issued in connection with U.S. Appl. No. 11/853,790, mailed Mar. 8, 2011, 12 pages.

"UPnP; "Universal Plug and Play Device Architecture"; Jun. 8, 2000; version 1.0; Microsoft Corporation; pp. 1-54".

Voyetra; Turtle Beach Inc., "Audio Tron Quick Start Guide, Version 1.0", Mar. 2001, 24 pages.

Voyetra; Turtle Beach Inc., "Audio Tron Reference Manual, Version 3.0", May 2002, 70 pages.

Voyetra; Turtle Beach Inc., "Audio Tron Setup Guide, Version 3.0", May 2002, 38 pages.

"Yamaha DME 32 manual": copyright 2000, pp. 296.

The United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 13/896,829, mailed on Jun. 12, 2014, 54 pages.

The United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 13/896,829, mailed on Jan. 7, 2014, 9 pages.

The United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 14/256,434, mailed on Jul. 23, 2014, 12 pages.

The United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 13/083,499, mailed on Jun. 2, 2014, 5 pages.

"Yamaha DME 64 Owner's Manual; copyright 2004, 80 pages".

"Yamaha DME Designer 3.5 set-up manual guide; copyright 2004, 16 pages".

Yamaha, "DME Designer 3.5 User Manual", Copyright 2004, 507 pages. (Document uploaded in 5 different files:—. NPL28_part1 pp. 1 to 128,—. NPL28_part2 pp. 129 to 263—. NPL28_part3 pp. 264 to 378—. NPL28_part4 pp. 379 to 471—. NPL28_part5 pp. 472 to 507).

The United States Patent and Trademark Office, "Final Office Action," issued in connection with U.S. Appl. No. 13/896,037, mailed on Jul. 23, 2014, 12 pages.

The United States Patent and Trademark Office, "Notice of Allowance", issued in connection with U.S. Appl. No. 13/892,230, mailed on Sep. 10, 2014, 5 pages.

Canadian Patent Office "Office Action", issued in connection with Canadian Patent Application No. 2,832,542, mailed on Apr. 10, 2015, 3 pages.

Dorwaldt Carl, "EASE 4.1 Tutorial", Renkus-Heinz, Inc., 2004, 417 pages.(NPL uploaded in 3 parts).

United States Patent and Trademark Office, "Non-Final Office Action" issued in connection with U.S. Appl. No. 14/299,847, mailed on Mar. 23, 2015, 14 pages.

Notice of Allowance mailed on Jul. 10, 2015, issued in connection with U.S. Appl. No. 13/013740, filed Jan. 25, 2011, 9 pages.

"Corrected Notice of Allowance mailed on Oct. 30, 2015, issued in connection with U.S. Appl. No. 13/013,740, filed Jan. 25, 2011, 2 pages."

"Notice of Allowance mailed on May 13, 2015, issued in connection with U.S Appl. No. 14/299,847, filed Jun. 9, 2014, 10 pages."

Notice of Allowance mailed on Oct. 27, 2015, issued in connection with U.S. Appl. No. 14/299,847, filed Jun. 9, 2014, 5 pages.

United States Patent and Trademark Office, "Non-Final Office Action", issued in connection with U.S. Appl. No. 13/013,740, mailed on Feb. 13, 2015, 14 pages.

United States Patent and Trademark Office, "Notice of Allowance", issued in connection with U.S. Appl. No. 14/256,434, mailed on Dec. 5, 2014, 7 pages.

Intellectual Property Office of Japan, "Office action", issued in connection with Japanese patent application No. 2014-503273, issue on Jan. 6, 2015, 5 pages.

* cited by examiner


100
Zone Player
102
Zone Player
104
Zone Player
106
140
142
108
Internet
music
110
112
Audio source

FIG. 1


200
202
216
217
204
206
210
212
214
Network Interface
Wireless
Wired
Processor
Memory
Audio Processing Circuit
Module
Audio Amplifier

FIG. 2A


240
Scroll Wheel 250
252
254
248
246
244
242
268
266
262
264
music
back
zones
ok
Rincon
Now Playing
image
vol

FIG. 2B


270
282
284
Memory
Application Module
Screen
Screen Driver
Micro Controller
RF Interface (Network Interface)
Input Interface
272
274
276
278
280

FIG. 2C


Zone Configuration/Scene
Bathroom
Bedroom
Den
Dining Room
Family Room
Foyer
Bathroom
Bedroom
Den
Dining Room
Family Room
Foyer

FIG. 3A

FIG. 3B


Bathroom
Bedroom
Den
Dining Room
Family Room
Foyer
Garage
Garden
Bathroom
Bedroom
Den
Dining Room
Family Room
Foyer
Garage
Garden


Master Bedroom
Kitchen
Patio
400
New Alarm
Alarm (On)
Time (7:15am)
Zone (Master Bedroom + linked zones)
Music (Wakeup Playlist)
Frequency (Weekdays)
Alarm length (45mins)
Play Alarm Now
Save Alarm
How often should the alarm sound?
Once
Weekdays
Weekends
Every Day

FIG. 4


500
Zone Scene: Morning
Your Zones
Hallway
Kitchen
Library
Living Room
Master Bedroom
Media Room
Add>>
<<Remove
Zone Scene
Bedroom
Den
Dining Room
Family Room
Foyer
Garage
Garden
Guest Room
Volumes...
Zones that are not added to the Scene will not be affected.
OK
Cancel
Apply

FIG. 5A


520
Zone Menu
Select the zones in this group
Bedroom
Kitchen
Dining Room
Living Room
Office
Patio
Check
Uncheck
Done

FIG. 5B


510
Volumes
Set the Volumes for the Zones in the Zone Sctne
Use the existing volume settings of the zone(s)
Unmute any Zones in the group that are muted
Adjust the volumes
Bedroom
Den
Dining Room
Family Room
Foyer
Unmute any Zones in the group that are muted
OK
Cancel
Apply

FIG. 5C


600
Start
602
configure a zone scene
604
decide which zone players to be associated with the scene
606
save the scene with parameters
610
invoke a zone scene
612
check status of zone players in the scene
614
execute commands to synchronize the zone players

FIG. 6

METHOD AND APPARATUS FOR UPDATING ZONE CONFIGURATIONS IN A MULTI-ZONE SYSTEM

CROSS REFERENCE TO RELATED APPLICATION

This application is a continuation of and claims priority to U.S. patent application Ser. No. 13/896,829, filed on May 17, 2013, entitled "METHOD AND APPARATUS FOR UPDATING ZONE CONFIGURATIONS IN A MULTI-ZONE SYSTEM" and to U.S. patent application Ser. No. 11/853,790, filed Sep. 11, 2007, entitled "CONTROLLING AND MANIPULATING GROUPINGS IN A MULTI-ZONE MEDIA SYSTEM," and U.S. Provisional Application No. 60/825,407 filed on Sep. 12, 2006, entitled "CONTROLLING AND MANIPULATING GROUPINGS IN A MULTI-ZONE MEDIA SYSTEM," each of which is hereby incorporated by reference in its entirety for all purposes.

BACKGROUND OF THE INVENTION

Field of the Invention

The invention is generally related to the area of consumer electronics and human-computer interaction. In particular, the invention is related to method and apparatus for controlling or manipulating a plurality of multimedia players in a multi-zone system.

An enduring passion for quality audio reproduction or system is continuing to drive demands from users. One of the demands includes an audio system in a house in which, for example, one could grill to classic rock on a patio while another one may cook up his/her own music selections in a kitchen. This is all at the same time while a teenager catches a ballgame in a family room, and another one blasts pop in a bedroom. And the best part of such audio system is that each family member does not need his or her own stereo system—one system gives everyone access to all the music sources.

Currently, one of the systems that can meet part of such demand is a conventional multi-zone audio system that usually includes a number of audio players. Each of the audio players has its own amplifier(s) and a set of speakers and typically installed in one place (e.g., a room). In order to play an audio source at one location, the audio source must be provided locally or from a centralized location. When the audio source is provided locally, the multi-zone audio system functions as a collection of many stereo systems, making source sharing difficult. When the audio source is provided centrally, the centralized location may include a juke box, many compact discs, an AM or FM radio, tapes, or others. To send an audio source to an audio player demanding such source, a cross-bar type of device is used to prevent the audio source from going to other audio players that may be playing other audio sources.

In order to achieve playing different audio sources in different audio players, the traditional multi-zone audio system is generally either hard-wired or controlled by a pre-configured and pre-programmed controller. While the pre-programmed configuration may be satisfactory in one situation, it may not be suitable for another situation. For example, a person would like to listen to broadcast news from his/her favorite radio station in a bedroom, a bathroom and a den while preparing to go to work in the morning. The same person may wish to listen in the den and the living room to music from a compact disc in the evening. In order to satisfy such requirements, two groups of audio players must be established. In the morning, the audio players in the bedroom, the bathroom and the den need to be grouped for the broadcast news. In the evening, the audio players in the den and the living room are grouped for the music. Over the weekend, the audio players in the den, the living room, and a kitchen are grouped for party music. Because the morning group, the evening group and the weekend group contain the den, it can be difficult for the traditional system to accommodate the requirement of dynamically managing the ad hoc creation and deletion of groups.

There is a need for dynamic control of the audio players as a group. With a minimum manipulation, the audio players may be readily grouped. In a traditional multi-zone audio system, the audio players have to be adjusted one at a time, resulting in an inconvenient and non-homogenous audio environment. Further, there is a need to individually or systematically adjust the audio volume of the audio players.

SUMMARY OF THE INVENTION

This section is for the purpose of summarizing some aspects of the present invention and to briefly introduce some preferred embodiments. Simplifications or omissions in this section as well as in the abstract or the title of this description may be made to avoid obscuring the purpose of this section, the abstract and the title. Such simplifications or omissions are not intended to limit the scope of the present invention.

In general, the present invention pertains to controlling a plurality of multimedia players, or simply players, in groups. According to one aspect of the present invention, a mechanism is provided to allow a user to group some of the players according to a theme or scene, where each of the players is located in a zone. When the scene is activated, the players in the scene react in a synchronized manner. For example, the players in the scene are all caused to play an audio source or music in a playlist, wherein the audio source may be located anywhere on a network.

According to another aspect of the present invention, the scene may be activated at any time or a specific time. A user may activate the scene at any time so that only some selected zones in an entertainment system facilitate a playback of an audio source. When the scene is activated at a specific time, the scene may be used as an alarm or buzzer.

According to still another aspect of the present invention, a controlling device (also referred to herein as controller) is provided to facilitate a user to select any of the players in the system to form respective groups each of which is set up per a scene. Although various scenes may be saved in any of the members in a group, commands are preferably sent from the controller to the rest of the members when one of the scenes is executed. Depending on implementation, the commands include parameters pertaining to identifiers of the players, volumes settings, audio source and etc.

According to yet another aspect of the present invention, a configurable module is implemented in the controlling device that provides interactive graphic user interface for forming, managing and controlling groups in the system, de-grouping a group or adjusting audio volume of individual players or a group of players.

The present invention may be implemented in many forms including software, hardware or a combination of both. According to one embodiment, the present invention is directed to a method for groupings in a multi-zone media system, the method comprises providing a mechanism to allow a user to determine which players in the system to be associated with a theme representing a group; and configuring the theme with parameters pertaining to the players,

wherein the theme is activated at anytime or a specific time so that the players react in a synchronized manner. The players in a scene are synchronized to play a multimedia file when the scene is activated.

According to another embodiment, the present invention is directed to an entertainment system for grouping players, the system comprises: a plurality of players, each located in one zone; and a controller providing a mechanism to allow a user to select which of the players to be associated with a theme representing a group; and configure the theme with parameters pertaining to the selected players, wherein the theme is activated at anytime or a specific time so that the selected players react in a synchronized manner. As a result, the selected players are synchronized to play a multimedia that is in a digital format and retrieved from a source over a network.

One of the objects, features, and advantages of the present invention is to remotely control a plurality of multimedia players in a multi-zone system, playing and controlling the audio source synchronously if the players are grouped together, or playing and controlling the audio source individually if the players are disassociated with each other.

Other objects, features, and advantages of the present invention will become apparent upon examining the following detailed description of an embodiment thereof, taken in conjunction with the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings where:

FIG. **1** shows an exemplary configuration in which the present invention may be practiced;

FIG. **2**A shows an exemplary functional block diagram of a player in accordance with the present invention;

FIG. **2**B shows an example of a controller that may be used to remotely control one of more players of FIG. **2**A;

FIG. **2**C shows an exemplary internal functional block diagram of a controller in accordance with one embodiment of the present invention;

FIG. **3**A provides an illustration of one zone scene, where the left column shows the starting zone grouping—all zones are separate, the column on the right shows the effects of grouping the zones to make a group of 3 zones named after "Morning";

FIG. **3**B shows that a user defines multiple groups to be gathered at the same time;

FIG. **4** shows an exemplary user interface that may be displayed on a controller or a computer of FIG. **1**;

FIG. **5**A shows a user interface to allow a user to form a scene;

FIG. **5**B shows another user interface **520** to allow a user to form a scene;

FIG. **5**C shows a user interface to allow a user to adjust a volume level of the zone players in a zone scene individually or collectively; and

FIG. **6** shows a flowchart or process of providing a player theme or a zone scene for a plurality of players, where one or more of the players are placed in a zone.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The detailed description of the invention is presented largely in terms of procedures in terms of procedures, steps, logic blocks, processing, and other symbolic representations that directly or indirectly resemble the operations of data processing devices coupled to networks. These process descriptions and representations are typically used by those skilled in the art to most effectively convey the substance of their work to others skilled in the art. Numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will become obvious to those skilled in the art that the present invention may be practiced without these specific details. In other instances, well known methods, procedures, components, and circuitry have not been described in detail to avoid unnecessarily obscuring aspects of the present invention.

Reference herein to "one embodiment" or "an embodiment" means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one embodiment of the invention. The appearances of the phrase "in one embodiment" in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. Further, the order of blocks in process flowcharts or diagrams representing one or more embodiments of the invention do not inherently indicate any particular order nor imply any limitations in the invention.

Referring now to the drawings, in which like numerals refer to like parts throughout the several views. FIG. **1** shows an exemplary configuration **100** in which the present invention may be practiced. The configuration may represent, but not be limited to, a part of a residential home, a business building or a complex with multiple zones. There are a number of multimedia players of which three examples **102**, **104** and **106** are shown as audio devices. Each of the audio devices may be installed or provided in one particular area or zone and hence referred to as a zone player herein.

As used herein, unless explicitly stated otherwise, an audio source or audio sources are in digital format and can be transported or streamed over a data network. To facilitate the understanding of the present invention, it is assumed that the configuration **100** represents a home. Thus, the zone player **102** and **104** may be located in two of the bedrooms respectively while the zone player **106** may be installed in a living room. All of the zone players **102**, **104** and **106** are coupled directly or indirectly to a data network **108**. In addition, a computing device **110** is shown to be coupled on the network **108**. In reality, any other devices such as a home gateway device, a storage device, or an MP3 player may be coupled to the network **108** as well.

The network **108** may be a wired network, a wireless network or a combination of both. In one example, all devices including the zone players **102**, **104** and **106** are coupled to the network **108** by wireless means based on an industry standard such as IEEE 802.11. In yet another example, all devices including the zone players **102**, **104** and **106** are part of a local area network that communicates with a wide area network (e.g., the Internet).

Many devices on the network **108** are configured to download and store audio sources. For example, the computing device **110** can download audio sources from the Internet and store the downloaded sources locally for sharing with other devices on the Internet or the network **108**. The computing device **110** or any of the zone players can also be configured to receive streaming audio. Shown as a stereo system, the device **112** is configured to receive an analog audio source (e.g., from broadcasting) or retrieve a digital audio source (e.g., from a compact disk). The analog audio sources can be

converted to digital audio sources. In accordance with the present invention, the audio source may be shared among the devices on the network **108**.

Two or more zone players may be grouped together to form a new zone group. Any combinations of zone players and an existing zone group may be grouped together. In one instance, a new zone group is formed by adding one zone player to another zone player or an existing zone group.

Referring now to FIG. **2**A, there is shown an exemplary functional block diagram of a zone player **200** in accordance with the present invention. The zone player **200** includes a network interface **202**, a processor **204**, a memory **206**, an audio processing circuit **210**, a module **212**, and optionally, an audio amplifier **214** that may be internal or external. The network interface **202** facilitates a data flow between a data network (i.e., the data network **108** of FIG. **1**) and the zone player **200** and typically executes a special set of rules (i.e., a protocol) to send data back and forth. One of the common protocols used in the Internet is TCP/IP (Transmission Control Protocol/Internet Protocol). In general, a network interface manages the assembling of an audio source or file into smaller packets that are transmitted over the data network or reassembles received packets into the original source or file. In addition, the network interface **202** handles the address part of each packet so that it gets to the right destination or intercepts packets destined for the zone player **200**.

The network interface **202** may include one or both of a wireless interface **216** and a wired interface **217**. The wireless interface **216**, also referred to as a RF interface, provides network interface functions by a wireless means for the zone player **200** to communicate with other devices in accordance with a communication protocol (such as the wireless standard IEEE 802.11a, 802.11b or 802.11g). The wired interface **217** provides network interface functions by a wired means (e.g., an Ethernet cable). In one embodiment, a zone player includes both of the interfaces **216** and **217**, and other zone players include only a RF or wired interface. Thus these other zone players communicate with other devices on a network or retrieve audio sources via the zone player. The processor **204** is configured to control the operation of other parts in the zone player **200**. The memory **206** may be loaded with one or more software modules that can be executed by the processor **204** to achieve desired tasks. According to one aspect of the present invention, a software module implementing one embodiment of the present invention is executed, the processor **204** operates in accordance with the software module in reference to a saved zone group configuration characterizing a zone group created by a user, the zone player **200** is caused to retrieve an audio source from another zone player or a device on the network.

According to one embodiment of the present invention, the memory **206** is used to save one or more saved zone configuration files that may be retrieved for modification at any time. Typically, a saved zone group configuration file is transmitted to a controller (e.g., the controlling device **140** or **142** of FIG. **1**, a computer, a portable device, or a TV) when a user operates the controlling device. The zone group configuration provides an interactive user interface so that various manipulations or control of the zone players may be performed.

The audio processing circuit **210** resembles most of the circuitry in an audio playback device and includes one or more digital-to-analog converters (DAC), an audio preprocessing part, an audio enhancement part or a digital signal processor and others. In operation, when an audio source is retrieved via the network interface **202**, the audio source is processed in the audio processing circuit **210** to produce analog audio signals. The processed analog audio signals are then provided to the audio amplifier **214** for playback on speakers. In addition, the audio processing circuit **210** may include necessary circuitry to process analog signals as inputs to produce digital signals for sharing with other devices on a network.

Depending on an exact implementation, the module **212** may be implemented as a combination of hardware and software. In one embodiment, the module **212** is used to save a scene. The audio amplifier **214** is typically an analog circuit that powers the provided analog audio signals to drive one or more speakers.

Referring now to FIG. **2**B, there is shown an exemplary controller **240**, which may correspond to the controlling device **140** or **142** of FIG. **1**. The controller **240** may be used to facilitate the control of multi-media applications, automation and others in a complex. In particular, the controller **240** is configured to facilitate a selection of a plurality of audio sources available on the network, controlling operations of one or more zone players (e.g., the zone player **200**) through a RF interface corresponding to the RF interface **216** of FIG. **2**A. According to one embodiment, the wireless means is based on an industry standard (e.g., infrared, radio, wireless standard IEEE 802.11a, 802.11b or 802.11g). When a particular audio source is being played in the zone player **200**, a picture, if there is any, associated with the audio source may be transmitted from the zone player **200** to the controller **240** for display. In one embodiment, the controller **240** is used to synchronize more than one zone players by grouping the zone players in a group. In another embodiment, the controller **240** is used to control the volume of each of the zone players in a zone group individually or together.

The user interface for the controller **240** includes a screen **242** (e.g., a LCD screen) and a set of functional buttons as follows: a "zones" button **244**, a "back" button **246**, a "music" button **248**, a scroll wheel **250**, "ok" button **252**, a set of transport control buttons **254**, a mute button **262**, a volume up/down button **264**, a set of soft buttons **266** corresponding to the labels **268** displayed on the screen **242**.

The screen **242** displays various screen menus in response to a user's selection. In one embodiment, the "zones" button **244** activates a zone management screen or "Zone Menu", which is described in more details below. The "back" button **246** may lead to different actions depending on the current screen. In one embodiment, the "back" button triggers the current screen display to go back to a previous one. In another embodiment, the 'back" button negates the user's erroneous selection. The "music" button **248** activates a music menu, which allows the selection of an audio source (e.g., a song) to be added to a zone player's music queue for playback.

The scroll wheel **250** is used for selecting an item within a list, whenever a list is presented on the screen **242**. When the items in the list are too many to be accommodated in one screen display, a scroll indicator such as a scroll bar or a scroll arrow is displayed beside the list. When the scroll indicator is displayed, a user may rotate the scroll wheel **250** to either choose a displayed item or display a hidden item in the list. The "ok" button **252** is used to confirm the user selection on the screen **242**.

There are three transport buttons **254**, which are used to control the effect of the currently playing song. For example, the functions of the transport buttons may include play/pause and forward/rewind a song, move forward to a next song track, or move backward to a previous track. According to one embodiment, pressing one of the volume control buttons such as the mute button **262** or the volume up/down button **264** activates a volume panel. In addition, there are three soft buttons **266** that can be activated in accordance with the labels

268 on the screen 242. It can be understood that, in a multi-zone system, there may be multiple audio sources being played respectively in more than one zone players. The music transport functions described herein shall apply selectively to one of the sources when a corresponding one of the zone players or zone groups is selected.

FIG. 2C illustrates an internal functional block diagram of an exemplary controller 270, which may correspond to the controller 240 of FIG. 2B. The screen 272 on the controller 270 may be a LCD screen. The screen 272 communicates with and is commanded by a screen driver 274 that is controlled by a microcontroller (e.g., a processor) 276. The memory 282 may be loaded with one or more application modules 284 that can be executed by the microcontroller 276 with or without a user input via the user interface 278 to achieve desired tasks. In one embodiment, an application module is configured to facilitate grouping a number of selected zone players into a zone group and synchronizing the zone players for one audio source. In another embodiment, an application module is configured to control together the audio volumes of the zone players in a zone group. In operation, when the microcontroller 276 executes one of the application modules 284, the screen driver 274 generates control signals to drive the screen 272 to display an application specific user interface accordingly, more of which will be described below.

The controller 270 includes a network interface 280 referred to as a RF interface 280 that facilitates wireless communication with a zone player via a corresponding RF interface thereof. In one embodiment, the commands such as volume control and audio playback synchronization are sent via the RF interfaces. In another embodiment, a saved zone group configuration is transmitted between a zone player and a controller via the RF interfaces. The controller 270 may control one or more zone players, such as 102, 104 and 106 of FIG. 1. Nevertheless, there may be more than one controllers, each preferably in a zone (e.g., a room) and configured to control any one and all of the zone players.

In one embodiment, a user creates a zone group including at least two zone players from the controller 240 that sends signals or data to one of the zone players. As all the zone players are coupled on a network, the received signals in one zone player can cause other zone players in the group to be synchronized so that all the zone players in the group playback an identical audio source or a list of identical audio sources in a timely synchronized manner. Similarly, when a user increases the audio volume of the group from the controller, the signals or data of increasing the audio volume for the group are sent to one of the zone players and causes other zone players in the group to be increased together in volume and in scale.

According to one implementation, an application module is loaded in memory 282 for zone group management. When a predetermined key (e.g. the "zones" button 244) is activated on the controller 240, the application module is executed in the microcontroller 276. The input interface 278 coupled to and controlled by the microcontroller 276 receives inputs from a user. A "Zone Menu" is then displayed on the screen 272. The user may start grouping zone players into a zone group by activating a "Link Zones" or "Add Zone" soft button, or de-grouping a zone group by activating an "Unlink Zones" or "Drop Zone" button. The detail of the zone group manipulation will be further discussed below.

As described above, the input interface 278 includes a number of function buttons as well as a screen graphical user interface. It should be pointed out that the controller 240 in FIG. 2B is not the only controlling device that may practice the present invention. Other devices that provide the equivalent control functions (e.g., a computing device, a hand-held device) may also be configured to practice the present invention. In the above description, unless otherwise specifically described, it is clear that keys or buttons are generally referred to as either the physical buttons or soft buttons, enabling a user to enter a command or data.

One mechanism for 'joining' zone players together for music playback is to link a number of zone players together to form a group. To link a number of zone players together, a user may manually link each zone player or room one after the other. For example, there is a multi-zone system that includes the following zones.

Bathroom
Bedroom
Den
Dining Room
Family Room
Foyer

If the user wishes to link 5 of the 6 zone players using the current mechanism, he/she must start with a single zone and then manually link each zone to that zone. This mechanism may be sometimes quite time consuming. According to one embodiment, a set of zones can be dynamically linked together using one command. Using what is referred to herein as a theme or a zone scene, zones can be configured in a particular scene (e.g., morning, afternoon, or garden), where a predefined zone grouping and setting of attributes for the grouping are automatically effectuated.

For instance, a "Morning" zone scene/configuration command would link the Bedroom, Den and Dining Room together in one action. Without this single command, the user would need to manually and individually link each zone. FIG. 3A provides an illustration of one zone scene, where the left column shows the starting zone grouping—all zones are separate, the column on the right shows the effects of grouping the zones to make a group of 3 zones named after "Morning".

Expanding this idea further, a Zone Scene can be set to create multiple sets of linked zones. For example, a scene creates 3 separate groups of zones, the downstairs zones would be linked together, the upstairs zones would be linked together in their own group, and the outside zones (in this case the patio) would move into a group of its own.

In one embodiment as shown in FIG. 3B, a user defines multiple groups to be gathered at the same time. For example: an "Evening Scene" is desired to link the following zones:

Group 1
Bedroom
Den
Dining Room
Group 2
Garage
Garden

where Bathroom, Family Room and Foyer should be separated from any group if they were part of a group before the Zone Scene was invoked.

One important of the features, benefits and objects in the present invention is that that zones do not need to be separated before a zone scene is invoked. In one embodiment, a command is provided and links all zones in one step, if invoked. The command is in a form of a zone scene. After linking the appropriate zones, a zone scene command could apply the following attributes:

Set volumes levels in each zones (each zone can have a different volume) Mute/Unmute zones.
Select and play specific music in the zones.
Set the play mode of the music (Shuffle, Repeat, Shuffle-repeat)

Set the music playback equalization of each zone (e.g., bass treble).

A further extension of this embodiment is to trigger a zone scene command as an alarm clock function. For instance the zone scene is set to apply at 8:00 am. It could link appropriate zones automatically, set specific music to play and then stop the music after a defined duration. Although a single zone may be assigned to an alarm, a scene set as an alarm clock provides a synchronized alarm, allowing any zones linked in the scene to play a predefined audio (e.g., a favorable song, a predefined playlist) at a specific time or for a specific duration. If, for any reason, the scheduled music failed to be played (e.g., an empty playlist, no connection to a share, failed UPnP, no Internet connection for an Internet Radio station), a backup buzzer will sound. This buzzer will be a sound file that is stored in a zone player.

FIG. **4** shows an exemplary user interface **400** that may be displayed on a controller **142** or a computer **110** of FIG. **1**. The interface **400** shows a list of items that may be set up by a user to cause a scene to function at a specific time. In the embodiment shown in FIG. **4**, the list of items includes "Alarm", "Time", "Zone", "Music", "Frequency" and "Alarm length". "Alarm" can be set on or off. When "Alarm" is set on, "Time" is a specific time to set off the alarm. "Zone" shows which zone players are being set to play a specified audio at the specific time. "Music" shows what to be played when the specific time arrives. "Frequency" allows the user to define a frequency of the alarm. "Alarm length" defines how long the audio is to be played. It should be noted that the user interface **400** is provided herein to show some of the functions associated with setting up an alarm. Depending on an exact implementation, other functions, such as time zone, daylight savings, time synchronization, and time/date format for display may also be provided without departing from the present invention.

According to one embodiment, each zone player in a scene may be set up for different alarms. For example, a "Morning" scene includes three zone players, each in a bedroom, a den, and a dining room. After selecting the scene, the user may set up an alarm for the scene as whole. As a result, each of the zone players will be activated at a specific time.

FIG. **5**A shows a user interface **500** to allow a user to form a scene. The panel on the left shows the available zones in a household. The panel on the right shows the zones that have been selected and be grouped as part of this scene. Depending on an exact implementation of a user interface, Add/Remove buttons may be provided to move zones between the panels, or zones may be dragged along between panels.

FIG. **5**B shows another user interface **520** to allow a user to form a scene. The user interface **520** that may be displayed on a controller or a computing device, lists available zones in a system. A checkbox is provide next to each of the zones so that a user may check in the zones to be associated with the scene.

FIG. **5**C shows a user interface **510** to allow a user to adjust a volume level of the zone players in a zone scene individually or collectively. As shown in the user interface **510**, the 'Volumes . . . ' button (shown as sliders, other forms are possible) allows the user to affect the volumes of the associated zone players when a zone scene is invoked. In one embodiment, the zone players can be set to retain whatever volume that they currently have when the scene is invoked. Additionally the user can decide if the volumes should be unmuted or muted when the scene is invoked.

FIG. **6** shows a flowchart or process **600** of providing a player theme or a zone scene for a plurality of players, where one or more of the players are placed in a zone. The process **600** is presented in accordance with one embodiment of the present invention and may be implemented in a module to be located in the memory **282** of FIG. **2**C.

The process **600** is initiated only when a user decides to proceed with a zone scene at **602**. The process **600** then moves to **604** where it allows a user to decide which zone players to be associated with the scene. For example, there are ten players in a household, and the scene is named after "Morning". The user may be given an interface to select four of the ten players to be associated with the scene. At **606**, the scene is saved. The scene may be saved in any one of the members in the scene. In the example of FIG. **1**, the scene is saved in one of the zone players and displayed on the controller **142**. In operation, a set of data pertaining to the scene includes a plurality of parameters. In one embodiment, the parameters include, but may not be limited to, identifiers (e.g., IP address) of the associated players and a playlist. The parameters may also include volume/tone settings for the associated players in the scene. The user may go back to **602** to configure another scene if desired.

Given a saved scene, a user may activate the scene at any time or set up a timer to activate the scene at **610**. The process **600** can continue when a saved scene is activated at **610**. At **612**, upon the activation of a saved scene, the process **600** checks the status of the players associated with the scene. The status of the players means that each of the players shall be in condition to react in a synchronized manner. In one embodiment, the interconnections of the players are checked to make sure that the players communicate among themselves and/or with a controller if there is such a controller in the scene.

It is assumed that all players associated with the scene are in good condition. At **614**, commands are executed with the parameters (e.g., pertaining to a playlist and volumes). In one embodiment, data including the parameters is transported from a member (e.g., a controller) to other members in the scene so that the players are caused to synchronize an operation configured in the scene. The operation may cause all players to play back a song in identical or different volumes or to play back a pre-stored file.

One of the features, benefits and advantages in the present invention is to allow sets of related devices (controllers and operating components) to exist as a group without interfering with other components that are potentially visible on the same wired or wireless network. Each of the sets is configured to a theme or a scene.

The present invention has been described in sufficient detail with a certain degree of particularity. It is understood to those skilled in the art that the present disclosure of embodiments has been made by way of examples only and that numerous changes in the arrangement and combination of parts may be resorted without departing from the spirit and scope of the invention as claimed. While the embodiments discussed herein may appear to include some limitations as to the presentation of the information units, in terms of the format and arrangement, the invention has applicability well beyond such embodiment, which can be appreciated by those skilled in the art. Accordingly, the scope of the present invention is defined by the appended claims rather than the forgoing description of embodiments.

The invention claimed is:

1. A multimedia controller including a processor, the controller configured to:

receive, via a network interface, a zone configuration from a first independent playback device of a plurality of independent playback devices, wherein the zone configuration is configured via the controller and maintained at the first independent playback device, and

wherein the zone configuration characterizes one or more zone scenes, each zone scene identifying a group configuration associated with two or more of the plurality of independent playback devices; and

cause a selectable indication of the received zone configuration to be displayed, wherein the displayed selectable indication is selectable to cause one or more of the zone scenes to be invoked by two or more of the plurality of independent playback devices.

2. The multimedia controller of claim **1**, wherein causing the selectable indication of the received zone configuration to be displayed comprises causing an indication of at least one of the one or more zone scenes to be displayed.

3. The multimedia controller of claim **2**, wherein causing the selectable indication of the at least one of the one or more zone scenes to be displayed comprises displaying an indication of the group configuration identified by the at least one of the one or more zone scenes to be displayed.

4. The multimedia controller of claim **3**, wherein the indication of the group configuration identified by the at least one of the one or more zone scenes comprises one group of independent playback devices.

5. The multimedia controller of claim **4**, further configured to:

after causing the indication of the received zone configuration to be displayed, cause one of the at least one of the one or more zone scenes to be activated.

6. The multimedia controller of claim **3**, wherein the indication of the group configuration identified by the at least one of the one or more zone scenes comprises two or more groups of independent playback devices.

7. The multimedia controller claim **1**, further configured to:

before receiving the zone configuration, send, to one of the plurality of independent playback devices, a command to save at least one of the one or more zone scenes.

8. The multimedia controller of claim **7**, wherein the command to save at least one of the one or more zone scenes includes, for each of the at least one or more zone scenes, (a) an indication of the two or more of the plurality of independent playback devices identified by the zone scene and (b) at least one other parameter pertaining to the scene.

9. The multimedia controller of claim **8**, wherein the at least one other parameter pertaining to the scene is one or more of (i) a volume level, (ii) a specific music, (iii) a play mode, or (iv) an equalization.

10. The multimedia controller of claim **1**, further configured to:

after causing the selectable indication of the received zone configuration to be displayed, cause at least one of the one or more zone scenes to be activated.

11. The multimedia controller of claim **1**, wherein each of the one or more zone scenes is associated with a name.

12. In a network comprising a plurality of independent playback devices, a method comprising:

receiving, via the network by a controller device, a zone configuration from a first independent playback device of a plurality of independent playback devices, wherein the zone configuration is configured via the controller and maintained at the first independent playback device, and wherein the zone configuration characterizes one or more zone scenes, each zone scene identifying a group configuration associated with two or more of the plurality of independent playback devices; and

causing, by the controller device, a selectable indication of the received zone configuration to be displayed, wherein the displayed selectable indication is selectable to cause one or more of the zone scenes to be invoked by two or more of the plurality of independent playback devices.

13. The method of claim **12**, wherein causing the selectable indication of the received zone configuration to be displayed comprises causing an indication of at least one of the one or more zone scenes to be displayed.

14. The method of claim **13**, wherein causing the selectable indication of the at least one of the one or more zone scenes to be displayed comprises displaying an indication of the group configuration identified by the at least one of the one or more zone scenes to be displayed.

15. The method of claim **12**, further comprising:

before receiving the zone configuration, sending, to one of the plurality of independent playback devices, a command to save at least one of the one or more zone scenes.

16. The method of claim **12**, further comprising:

after causing the selectable indication of the received zone configuration to be displayed, causing, by the controller device, at least one of the one or more zone scenes to be activated.

17. A non-transitory computer-readable storage medium including a set of instructions for execution by a processor, the set of instructions, when executed, implement a controller configured to:

receive, via a network interface, a zone configuration from a first independent playback device of a plurality of independent playback devices, wherein the zone configuration is configured via the controller and maintained at the first independent playback device, and wherein the zone configuration characterizes one or more zone scenes, each zone scene identifying a group configuration associated with two or more of the plurality of independent playback devices; and

cause a selectable indication of the received zone configuration to be displayed, wherein the displayed selectable indication is selectable to cause one or more of the zone scenes to be invoked by two or more of the plurality of independent playback devices.

18. The computer-readable medium of claim **17**, wherein causing the selectable indication of the received zone configuration to be displayed comprises causing an indication of at least one of the one or more zone scenes to be displayed.

19. The computer readable medium of claim **17**, wherein causing the selectable indication of the at least one of the one or more zone scenes to be displayed comprises displaying an indication of the group configuration identified by the at least one of the one or more zone scenes to be displayed.

20. The computer readable medium of claim **19**, wherein the indication of the group configuration identified by the at least one of the one or more zone scenes comprises two or more groups of independent playback devices.

* * * * *